



MM2-2FXM2

Industrial Networking: Industrial Ethernet: MICE: ETHERNET / Fast-ETHERNET Media Modules

Product description

Description	Media module for MICE Switches (MS...), 100BASE-FX multi-mode F/O
Port type and quantity	2 x 100BASE-FX, MM cable, SC sockets
Type	MM2-2FXM2
Order No.	943 718-101

Network size - length of cable

Multimode fiber (MM) 50/125 µm	0 - 5000 m 8 dB link budget at 1300 nm A = 1 dB/km, 3 dB reserve, B = 800 MHz x km
Multimode fiber (MM) 62.5/125 µm	0 - 4000 m 11 dB link budget at 1300 nm A = 1 dB/km, 3 dB reserve, B = 500 MHz x km

Power requirements

Operating voltage	power supply via the backplane of the MICE switch
Power consumption	5 W

Service

Diagnostics	LEDs (power, link status, data, 100 Mbit/s, full duplex, ring port, LED test)
-------------	---

Ambient conditions

Operating temperature	0 °C to +60 °C
Storage/transport temperature	-40 °C to +70 °C
Relative humidity (non-condensing)	10% to 95%
MTBF	83.5 years; MIL-HDBK 217F: Gb 25 °C

Mechanical construction

Dimensions (W x H x D)	38 mm x 134 mm x 77 mm
Mounting	DIN Rail 35 mm
Weight	170 g
Protection class	IP 20

Mechanical stability

IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)

EMC emitted immunity

FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A

Approvals

Safety of industrial control equipment	cUL 508 (E175531)
Hazardous locations	cUL 1604 Class 1 Div 2 (E203960)
Germanischer Lloyd	Germanischer Lloyd (43 109-02 HH)

Scope of delivery and accessories

Scope of delivery	module, operating manual
Accessories to order separately	ML-MS2/MM labels