



Product information SPIDER III - Standard Line (SL) and Premium Line (PL) - SPIDER-PL-20-04T1S29999TX9HHHH

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-437329-498960/en/SPIDER-PL-20-04T1S29999TX9HHHH/ulistate>

Name SPIDER III - Standard Line (SL) and Premium Line (PL)



Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, 10/100 Mbit/s Ethernet

Delivery informations

Availability available

Product description

Description Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, 10/100 Mbit/s Ethernet

Port type and quantity 4x 10/100BASE-TX, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity, 1 x 100BASE-FX, SM cable, SC sockets

Type SPIDER-PL-20-04T1S29999TX9HHHH

Order No. 942141126

More Interfaces

Power supply/signaling contact 1 x plug-in terminal block, 6-pin

USB interface 1 x USB for configuration

Network size - length of cable

Twisted pair (TP) 0 m ... 100 m

Single mode fiber (SM) 9/125 µm 0 - 30 km (Link Budget at 1300 nm = 0 - 16 db; A = 0.4 dB/km; BLP = 3.5 ps/(nm*km))

Network size - cascadiability

Line - / star topology any

Power requirements

Operating voltage 12/24 V DC (9.6 - 32 V DC), redundant

Current consumption at 24 V DC Max. 180 mA

Power consumption Max. 4.3 W, 14.7 Btu (IT) h

Ambient conditions

Operating temperature -40 °C ... 70 °C

Storage/transport temperature -40 °C ... 85 °C

Relative humidity (non-condensing) 0 % ... 95 %

MTBF (Telcordia) 1.059.586 hours; Telcordia SR-332; Gb 25°C

Mechanical construction

Dimensions (W x H x D) 39 x 135 x 117 mm (w/o terminal block)

Mounting DIN Rail

Weight 430 g

Protection class IP40 (metal housing)

Mechanical stability

IEC 60068-2-27 shock 15 g, 11 ms duration, 18 shocks

IEC 60068-2-6 vibration 3.5 mm, 5-8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4-150 Hz, 10 cycles, 1 octave/min

Configurable parameters

Configurable parameters Global settings: power supply unit alarm, aging time, QoS 802.1p mapping, QoS DSCP mapping; Port settings: flow control, port admin state, broadcast storm protection/threshold, multicast storm protection/threshold, QoS Trust Mode, port based priority, link alarm; TX port settings: auto-negotiation, speed, duplex mode, auto-crossing, MDI state, energy efficient ethernet; FX port settings: duplex mode

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD) 4 kV contact discharge, 8 kV air discharge

EN 61000-4-3 electromagnetic field 10 V/m (80-1000 MHz)

EN 61000-4-4 fast transients (burst) 2 kV power line, 4 kV data line

EN 61000-4-5 surge voltage power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line

EN 61000-4-6 conducted immunity 10 V (150 kHz-80 MHz)



HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-437329-498960/en/SPIDER-PL-20-04T1S29999TX9HHHH/ulistate>

EMC emitted immunity

FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
-------------------	----------------------------

EN 55022	EN 55022 Class A
----------	------------------

Service

Diagnostics	LEDs (power, link status, data, data rate)
-------------	--

Approvals

Safety of industrial control equipment	cUL61010
--	----------

Hazardous locations	ISA-12.12.-01 Class 1 Div. 2 Group
---------------------	------------------------------------

Scope of delivery and accessories

Scope of delivery	Device, terminal block, safety instruction
-------------------	--

Accessories	Rail Power Supply RPS 30/80 EEC/120 EEC (CC), Wall mounting plate for DIN rail mounting 40mm - order nr. 942 177-001, wall mounting plate for DIN rail mounting 70mm - order nr. 942 177-002
-------------	--

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.