



Product information SPIDER III - Standard Line (SL) and Premium Line (PL) - SPIDER-SL-20-05T1999999TY9HHHH

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-437329-498960/en/SPIDER-SL-20-05T1999999TY9HHHH/uistate>

Name		SPIDER III - Standard Line (SL) and Premium Line (PL)
		
		Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, 10/100 Mbit/s Ethernet
Delivery informations		
Availability	available	
Product description		
Description	Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, 10/100 Mbit/s Ethernet	
Port type and quantity	5x 10/100BASE-TX, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity	
Type	SPIDER-SL-20-05T1999999TY9HHHH	
Order No.	942 132-016	
More Interfaces		
Power supply/signaling contact	1 x plug-in terminal block, 3-pin	
Network size - length of cable		
Twisted pair (TP)	0 m ... 100 m	
Network size - cascability		
Line - / star topology	any	
Power requirements		
Operating voltage	12/24 V DC (9,6 - 32 V DC)	
Current consumption at 24 V DC	Max. 55 mA	
Power consumption	Max. 1.3 W, 4.6 Btu (IT) h	
Ambient conditions		
Operating temperature	-40 °C ... 70 °C	
Storage/transport temperature	-40 °C ... 85 °C	
Relative humidity (non-condensing)	0 % ... 95 %	
MTBF (Telcordia)	2.845.546 hours; Telcordia SR-332; Gb 25°C	
Mechanical construction		
Dimensions (W x H x D)	26 x 102 x 79 mm (w/o terminal block)	
Mounting	DIN Rail	
Weight	120 g	
Protection class	IP30	
Mechanical stability		
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks	
IEC 60068-2-6 vibration	3.5 mm, 5-8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4-150 Hz, 10 cycles, 1 octave/min	
EMC interference immunity		
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge	
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)	
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line	
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line	
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)	
EMC emitted immunity		
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A	
EN 55022	EN 55022 Class A	
Service		
Diagnostics	LEDs (power, link status, data, data rate)	
Approvals		
Safety of industrial control equipment	cUL61010	



HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-437329-498960/en/SPIDER-SL-20-05T199999TY9HHHH/ulistate>

Scope of delivery and accessories

Scope of delivery	Device, terminal block, safety instruction
Accessories	Rail Power Supply RPS 30/80 EEC/120 EEC (CC), Wall mounting plate for DIN rail mounting 40mm - order nr. 942 177-001, wall mounting plate for DIN rail mounting 70mm - order nr. 942 177-002

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.