




## Product information SPIDER III - Standard Line (SL) and Premium Line (PL) - SPIDER-SL-20-06T1S29999SY9HHHH

Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-437329-498960/en/SPIDER-SL-20-06T1S29999SY9HHHH/uistate>

<b>Name</b>		SPIDER III - Standard Line (SL) and Premium Line (PL)
		
		Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, 10/100 Mbit/s Ethernet
<b>Delivery informations</b>		
<b>Availability</b>	available	
<b>Product description</b>		
<b>Description</b>	Unmanaged, Industrial ETHERNET Rail Switch, fanless design, store and forward switching mode, 10/100 Mbit/s Ethernet	
<b>Port type and quantity</b>	6x 10/100BASE-TX, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity, 1 x 100BASE-FX, SM cable, SC sockets	
<b>Type</b>	SPIDER-SL-20-06T1S29999SY9HHHH	
<b>Order No.</b>	942 132-011	
<b>More Interfaces</b>		
<b>Power supply/signaling contact</b>	1 x plug-in terminal block, 3-pin	
<b>Network size - length of cable</b>		
<b>Twisted pair (TP)</b>	0 m ... 100 m	
<b>Single mode fiber (SM) 9/125 µm</b>	0 - 30 km (Link Budget at 1300 nm = 0 - 16 db; A = 0.4 dB/km; BLP = 3.5 ps/(nm*km))	
<b>Network size - cascadiability</b>		
<b>Line - / star topology</b>	any	
<b>Power requirements</b>		
<b>Operating voltage</b>	12/24 V DC (9,6 - 32 V DC)	
<b>Current consumption at 24 V DC</b>	Max. 120 mA	
<b>Power consumption</b>	Max. 2,8 W, 9,5 Btu (IT) h	
<b>Ambient conditions</b>		
<b>Operating temperature</b>	0 °C ... 60 °C	
<b>Storage/transport temperature</b>	-40 °C ... 70 °C	
<b>Relative humidity (non-condensing)</b>	0 % ... 95 %	
<b>MTBF (Telcordia)</b>	1.554.703 hours; Telcordia SR-332; Gb 25°C	
<b>Mechanical construction</b>		
<b>Dimensions (W x H x D)</b>	45 x 110 x 88 mm (w/o terminal block)	
<b>Mounting</b>	DIN Rail	
<b>Weight</b>	210 g	
<b>Protection class</b>	IP30	
<b>Mechanical stability</b>		
<b>IEC 60068-2-27 shock</b>	15 g, 11 ms duration, 18 shocks	
<b>IEC 60068-2-6 vibration</b>	3.5 mm, 5-8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4-150 Hz, 10 cycles, 1 octave/min	
<b>EMC interference immunity</b>		
<b>EN 61000-4-2 electrostatic discharge (ESD)</b>	4 kV contact discharge, 8 kV air discharge	
<b>EN 61000-4-3 electromagnetic field</b>	10 V/m (80-1000 MHz)	
<b>EN 61000-4-4 fast transients (burst)</b>	2 kV power line, 4 kV data line	
<b>EN 61000-4-5 surge voltage</b>	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line	
<b>EN 61000-4-6 conducted immunity</b>	10 V (150 kHz-80 MHz)	
<b>EMC emitted immunity</b>		
<b>FCC CFR47 Part 15</b>	FCC 47 CFR Part 15 Class A	
<b>EN 55022</b>	EN 55022 Class A	
<b>Service</b>		
<b>Diagnostics</b>	LEDs (power, link status, data, data rate)	



# HIRSCHMANN

A BELDEN BRAND

## Industrial Ethernet:Unmanaged Industrial Ethernet Switches:SPIDER III-Switches:SPIDER III - Standard Line (SL) and Premium Line (PL)

<https://www.e-catalog.beldensolutions.com:443/link/57078-24455-49855-437329-498960/en/SPIDER-SL-20-06T1S29999SY9HHHH/ulistate>

### Approvals

Safety of industrial control equipment	cUL61010
--	----------

### Scope of delivery and accessories

Scope of delivery	Device, terminal block, safety instruction
-------------------	--

Accessories	Rail Power Supply RPS 30/80 EEC/120 EEC (CC), Wall mounting plate for DIN rail mounting 40mm - order nr. 942 177-001, wall mounting plate for DIN rail mounting 70mm - order nr. 942 177-002
-------------	--

For more information please contact:

**Hirschmann Automation and Control GmbH**

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: [inet-sales@belden.com](mailto:inet-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.